

County Surveyor's Record, Douglas County, Oregon

16867

Subdivision, Sec. 13,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
23.10	Camp Creek Road, asphalt surface, 25 lks. wide, bears N. 20° E. and S. 20° W.
33.75	Creek, 5 lks. wide, course N. 75° W.; desc. 15 ft. over nearly level bottom land.
54.95	Camp Crekk, 10 lks. wide, course N. 20° E.; asc. 250 ft. over SE. slope.
63.25	Road, asphalt surface, 25 lks. wide, bears N. 45° E. and S. 45° W.
69.30	Spur, slopes N. 80° E.; desc. 205 ft. over NE. slope.
74.88	The E 1/16 sec. cor. of secs. 12 and 13, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	E 1/16 $\frac{S\ 12}{S\ 13}$ 1969
	from which bearing trees mkd. by Jelley and Steward
	A hemlock, 8 ins. diam., bears S. 13 3/4° E., 16 1/2 lks. dist., with scribe marks E 1/16 S13 BT visible on open blaze.
	A hemlock, 10 ins. diam., bears N. 12 1/2° W., 24 lks. dist., with healed blaze. (Record, N. 84 3/4° W., 20 lks.)
	From the N. 1/16 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.
	N 1/16 S 13 1969
	from which bearing trees mkd. by Jelley and Steward
	A fir, 18 ins. diam., bears S. 17 1/4° W., 62 lks. dist., with healed blaze.
	A hemlock, 13 ins. diam., bears N. 89 3/4° W., 32 lks. dist., with healed blaze.
	N. 89° 42' W., on the E. and W. center line of the NE 1/4 of sec. 13.
	Desc. 115 ft. over SW. slope, through logged area.
12.50	Spur, slopes S. 80° W.; desc. 155 ft. over NW slope.; also enter timber, edge bears N. 30° E. and S. 30° W.
18.935	The NE. 1/16 sec. cor. of sec. 13.
	Desc. 15 ft. over nearly level land.
20.25	Camp Creek Road, asphalt surface 25 lks. wide, bears N. 25° E. and S. 25° W.