

# County Surveyor's Record, Douglas County, Oregon

16870

Subdivision, Sec. 13,  
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>SW 1/16 S 13 1981</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 41 ins. diam., bears N. 4° E., 76 lks. dist., mkd. SW 1/16 S13 BT.</p> <p style="padding-left: 40px;">A hemlock, 16 ins. diam., bears S. 78° E., 115 lks. dist., mkd. SW 1/16 S13 BT.</p> <p>Asc. 105 ft. over SE. slope.</p>
24.80	Spur, slopes N. 80° E.; desc. 250 ft. over N. slope.
36.20	Creek, 3 lks. wide, course S. 80° E.; asc. 45 ft. over SW. slope.
39.39	The center W. 1/16 sec. cor. of sec. 13.
	<p>From the center S. 1/16 sec. cor. of sec. 13.</p> <p>N. 89° 31' W., on the E. and W. center line of the SW 1/4 of sec. 13.</p> <p>Asc. 75 ft. over SE. slope, through moderate timber and undergrowth.</p>
19.65	<p>The SW. 1/16 sec. cor. of sec. 13.</p> <p>Asc. 370 ft. over SE. slope.</p>
26.15	Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.
35.35	Spur, slopes N. 70° E.; desc. 95 ft. over NW. slope.
38.75	Ravine, drains N. 40° E.; asc. 20 ft. over NE. slope.
39.32	The S. 1/16 sec. cor. of secs. 13 and 14, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	<p>S 1/16 S 14   S 13 1969</p>
	<p>from which bearing trees mkd. by Jelley and Steward</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears S. 32 1/4° E., 36 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 75 ins. diam., bears N. 33° W., 16 lks. dist., with scribe marks 16 S14 visible on open blaze.</p>
	<p>From the center W. 1/16 sec. cor. of sec. 13.</p> <p>N. 0° 20' W., on the N. and S. center line of the NW 1/4 of sec. 13.</p> <p>Asc. 245 ft. over broken S. slope, through moderate timber and undergrowth.</p>