

# County Surveyor's Record, Douglas County, Oregon

16876

Dependent Resurvey, Portion of N. Bdy.,  
T. 29 S., R. 3 W., Willamette Mer., Oregon

CHAINS	
14.50	Ridge bears N. and S.; desc. 130 ft. over SW. slope, also gravelled road, 25 lks. wide, bears along ridge top.
14.75	Enter old growth timber, edge bears N. and S.
19.19	Point for the E 1/16 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<hr style="width: 20%; margin: auto;"/> <div style="display: flex; justify-content: center; gap: 20px;"> <span>E 1/16</span> <span>S 5</span> </div> <div style="text-align: center;">1980</div>
	from which
	A fir, 30 ins. diam., bears S. 67 1/2° E., 24 lks. dist., mkd. E 1/16 S5 BT.
	A fir, 22 ins. diam., bears S. 57° W., 50 lks. dist., mkd. E 1/16 S5 BT.
	Descend 145 ft. over SW. slope.
28.80	Creek, 1 lk. wide, course S. 35° W.; asc. 65 ft. over SE. slope.
30.15	Spur, slopes S. 10° W.; desc. 200 ft. over NW. slope.
38.38	The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the Tp., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.
	<div style="text-align: center;">                     COUNTY SURVEYORS OFFICE  <u>T 28 S    R 3 W</u>                      1/4      S 5                       T 29 S                      1962                 </div>
	from which a bearing tree mkd. by Gibb
	A fir, 15 ins. diam., bears S. 10° W., 9 lks. dist., with illegible scribe marks visible on partially healed blaze.
	and a bearing tree mkd. by Byron
	A fir, 10 ins. diam., bears S. 88° W., 28 lks. dist., with healed double blaze.
	<hr style="width: 20%; margin: auto;"/>
	West, beginning new measurement.
	Descend 155 ft. over NW. slope.
5.30	Letitia Creek, 5 lks. wide, course S. 25° W.; asc. 345 ft. over SE. slope.
11.17	From this point the original closing corner of secs. 31 and 32, T. 28 S., R. 3 W., bears N., 0.176 chs. dist., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.