

County Surveyor's Record, Douglas County, Oregon

16879

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Mer., Oregon

CHAINS

in 1959, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S R 3 W
S 21 | S 22
S 28 | S 27

1959

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears N. 5° E., 80 lks. dist., no marks visible.

A fir, 22 ins. diam., bears S. 16° E., 25 lks. dist., with healed blaze.

A laurel, 25 ins. diam., bears S. 10° W., 44 lks. dist., no marks visible.

A fir, 18 ins. diam., bears N. 13° W., 33 lks. dist., with healed blaze.

and bearing trees mkd. by Byron

A fir stump, 20 ins. diam., bears N. 36 1/2° E., 44 lks. dist., with scribe marks BT visible on opened blaze.

A fir, 10 ins. diam., bears S. 57° W., 84 lks. dist., with healed blaze.

and a new bearing tree

A fir, 12 ins. diam., bears N. 76° E., 68 lks. dist., mkd. T29S R3W S22 BT.

From this point, Douglas County, 2nd Order, Horizontal Control Station "Day," bears N. 82° 50' E., 82.11 chs. dist., monumented with a brass tablet, firmly set in concrete, flush with ground, with tablet mkd. "Day 1978."

N. 0° 30' W., bet. secs. 21 and 22, marking and blazing the true line.

Ascend 375 ft. over S. slope, through heavy timber and dense undergrowth.

23.85 Spur, slopes S. 50° E.; asc. 45 ft. over SE. slope.

37.80 Ridge bears E. and W.; desc. 45 ft. over NW. slope.

40.45 Point for the 1/4 sec. cor. of secs. 21 and 22, determined by the irregular boundary method; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W

1/4
S 21 | S 22

1980

from which