

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **16880**
T. 29 S., R. 3 W., Willamette Mer., Oregon

CHAINS

A fir, 7 ins. diam., bears S. 18° E., 25 lks.
dist., mkd. 1/4 S22 BT.

A fir, 8 ins. diam., bears S. 38 1/4° W., 46 lks.
dist., mkd. 1/4 S21 BT.

N. 0° 23' W., beginning new measurement.

Descend 245 ft. over NW. slope.

10.35 Ravine, drains W.; asc. 5 ft. over SW. slope.

15.10 Ravine, drains S. 50° W.; asc. 290 ft. over broken
SW. slope.

27.40 Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.

32.25 Ridge, bears N. 55° E. and S. 60° W.; desc. 250 ft. over
NW. slope.

40.14 The cor. of secs. 15, 16, 21, and 22, perpetuated and
recorded by James W. Byron, Deputy County Surveyor, in
1961, monumented with an iron post, 1 1/4 ins. diam., firmly
set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S
S 16 | S 15
S 21 | S 22
R 3 W

1961

from which the remains of the original bearing trees

A cedar, 30 ins. diam., bears N. 80° E., 70 lks.
dist., with axe marks visible on opened blaze.

A fir, 36 ins. diam., bears S. 75° E., 10 lks.
dist., with axe marks visible on opened blaze.

A cedar stump, 32 ins. diam., bears S. 65° W.,
71 lks. dist., with axe marks visible on opened
blaze. (Record, N. 5° W.)

A fir stump, 44 ins. diam., bears N. 2° W.,
56 lks. dist., with axe marks visible on opened
blaze. (Record, N. 5° W.)

and bearing trees mkd. by Byron

A fir, 11 ins. diam., bears N. 82° E., 33 lks.
dist., with healed blaze.

A pine, 21 ins. idam., bears S. 46° E., 84 lks.
dist., with healed blaze.

A fir, 19 ins. diam., bears S. 62° W., 45 lks.
dist., with healed blaze.

A fir, 20 ins. idam., bears N. 51° W., 14 lks.
dist., with illegible scribe marks visible on
opened blaze.