

County Surveyor's Record, Douglas County, Oregon

16882

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Mer., Oregon

CHAINS					
19.45	Spur, slopes S.; desc. 235 ft. over SW. slope.				
32.55	Ravine, drains S. 5° E.; asc. 160 ft. over SE. slope.				
39.60	Spur, slopes S. 10° E.; desc. 20 ft. over SW. slope.				
40.88	<p>The cor. of secs. 20, 21, 28, and 29, perpetuated and recorded by John N. Markham, Registered Logging Engineer No. 2880, in 1952, monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground,</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A laurel, 18 ins. diam., bears S. 70° W., 13 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A laurel, 16 ins. diam., bears N. 80° W., 14 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Powell</p> <p style="padding-left: 40px;">A madrone, 16 ins. diam., bears N. 22 1/2° E., 25 1/2 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears S. 86 1/2° E., 22 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 29 S R 3 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;">S 21</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 28</td> </tr> </table> <p>1980</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 57° E., 42 lks. dist., mkd. T29S R3W S21 BT.</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears S. 12° W., 77 lks. dist., mkd. T29S R3W S29 BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 46° W., 60 lks. dist., mkd. T29S R3W S20 BT.</p> <p>Reset iron pipe alongside iron post.</p> <p>Land, mountainous. Soil, rocky clay. Timber, yew, pine, fir, cedar, hemlock, maple, oak, and madrone; undergrowth, salal, Oregon grape, poison oak, fern, dogwood, blackberry, thimbleberry, hazel, arrowwood, and young timber.</p>	S 20	S 21	S 29	S 28
S 20	S 21				
S 29	S 28				
3.20	Spur, slopes S. 30° E.; asc. 15 ft. over SE. slope.				
6.10	Ridge, bears NE. and SW.; desc. 360 ft. over NW. slope.				
	<p>N. 0° 09' E., bet. secs. 20 and 21.</p> <p>Ascend 65 ft. over S. slope, through heavy timber and dense undergrowth.</p>				