

County Surveyor's Record, Douglas County, Oregon

16883

Dependent Resurvey, Portion of Subdivisional Lines,

T. 29 S. R. 3 W. Willamette Mer. Oregon

CHAINS	
22.75	Bottom of descent, drains W.; asc. 20 ft. over SW. slope.
30.50	Spur, slopes NW.; desc. 345 ft. over NW. slope, changing to N. slope.
40.35	The 1/4 sec. cor. of secs. 20 and 21, perpetuated and recorded by Arthur R. Evans, Deputy County Surveyor, in 1952, further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	<p>COUNTY SURVEYORS OFFICE</p> <p>1/4</p> <p>S 20 S 21</p> <p>T 29 S R 3 W</p> <p>1962</p>
	from which the remains of the original bearing trees
	A root hole, bears S. 3° E., 56 lks. dist., along-side of which is a fir, 35 ins. diam., no marks visible.
	A twin maple, 30 ins. diam., bears S. 60° W., 92 lks. dist., with axe marks visible on open blaze.
	and bearing tree by Evans
	A fir stump, 35 ins. diam., bears S. 70° W., 118 lks. dist., with scribe marks 1/4 S20 RE 2741 BT visible on bark blaze.
	and a bearing tree by Byron
	A fir, 20 ins. diam., bears N. 83° E., 33 lks. dist., with healed blaze.
	<hr style="width: 20%; margin: 10px auto;"/>
	N. 0° 11' W., beginning new measurement.
	Descend 15 ft. over gentle N. slope.
2.50	Enter open field, edge bears NE. and W.
13.55	South Myrtle Creek, 85 lks. wide, course S. 80° W.; asc. 10 ft. over S. slope.
15.95	Wood frame barn, 46 x 26 ft., the SE cor. bears west, 0.09 chs. dist., long side bears N. 65° W.
20.095	Point for the N 1/16 sec. cor. of secs. 20 and 21.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 42 ins. in the ground, with top 14 ins. below the surface of ground, with brass cap mkd.
	<p>N 1/16</p> <p>S 20 S 21</p> <p>1980</p>
	from which