

County Surveyor's Record, Douglas County, Oregon

16884

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Mer., Oregon

CHAINS

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 6 1/4° E., 193 lks. dist., with brass cap mkd. N 1/16 S21 RM 1980 and an arrow pointing to the corner.

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 6 1/4° W., 161 lks. dist., with brass cap mkd. N 1/16 S20 RM 1980 and an arrow pointing to the corner.

Cor. is located in open field.

Ascend 100 ft. over SE. slope.

22.35 South Myrtle Creek Road, asphalt surface, 40 lks. wide, bears N. 65° E. and S. 50° W., in curve.

26.00 Spur, slopes S. 50° E.; asc. 115 ft. over SE. slope.

36.60 Spur, slopes SW.; asc. 5 ft. along W. slope.

40.19 Point for the cor. of secs. 16, 17, 20, and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W

S 17	S 16
S 20	S 21

1980

from which bearing trees and a reference monument

A fir, 18 ins. diam., bears N. 10 1/2° E., 172 lks. dist., mkd. T29S R3W S16 BT.

A cedar, 18 ins. diam., bears S. 4° E., 278 lks. dist., mkd. T29S R3W S21 BT.

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 50° W., 35 lks. dist., with brass cap mkd. T29S R3W S20 RM 1980 and an arrow pointing to the corner.

A pine, 16 ins. diam., bears N. 63 1/2° W., 165 lks. dist., mkd. T29S R3W S17 BT.

Land, mountainous,
Soil, rocky clay loam,
Timber, fir, hemlock, cedar, maple, oak, myrtle, madrone, dogwood, and alder; undergrowth, salal, rhododendron, poison oak, Oregon grape, vine maple, hazel, fern, and grasses.

S 89° 39' W., bet. secs. 16 and 21.

Descend 535 ft. over NW. slope, through heavy timber and dense undergrowth.