

County Surveyor's Record, Douglas County, Oregon

16885

Dependent Resurvey, Portion of Subdivisional Lines
T. 29 S., R 3 W., Willamette Mer., Oregon

CHAINS	
40.05	South Myrtle Creek, 40 lks. wide, course S. 55° W., over nearly level creek bottom.
40.52	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 3 1/4 in. stem, in bedrock, with top mkd.</p>
	<p>T 29 S R 3 W</p> <p>1/4 $\frac{S\ 16}{S\ 21}$</p> <p>1980</p>
	from which
	<p>A fir, 12 ins. diam., bears N. 85 1/4° E., 110 lks. dist., mkd. 1/4 S16 BT.</p>
	<p>A cedar, 25 ins. diam., bears S. 81 1/2° W., 75 lks. dist., mkd. 1/4 S21 BT.</p>
	Ascend 10 ft. over nearly level land.
41.40	Creek, 2 lks. wide, course S. 30° E.; asc. 20 ft. over nearly level pasture land.
41.65	Barbed wire fence lines, bears N. 20° E. and S. 20° W.
47.65	Power line, bears N. 30° E. and S. 30° W.
51.60	Barbed wire fence lines, bears N. 35° E. and S. 20° W.
52.15	South Myrtle Creek Road, asphalt surface, 40 lks. wide, bears N. 35° E. and S. 35° W., enter moderate timber and undergrowth, also foot of hill, bears N. 35° E. and S. 35° W.; asc. 220 ft. over SE. slope.
57.75	Spur, slopes S. 20° W.; desc. 50 ft. over SW. slope.
60.78	<p>Point for the W 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>W 1/16 $\frac{S\ 16}{S\ 21}$</p> <p>1979</p>
	from which
	<p>A fir, 10 ins. diam., bears N. 49 1/4° E., 15 lks. dist., mkd. W 1/16 S16 BT.</p>
	<p>A fir, 10 ins. diam., bears S. 11 1/2° E., 50 lks. dist., mkd. W 1/16 S21 BT.</p>
	Descend 90 ft. over SW. slope.
64.75	Creek, 5 lks. wide, course S. 20° E.; asc. 270 ft. over broken SE. slope.
72.15	Enter open field, edge bears N. and S.
76.85	Spur, slopes S.; desc. 60 ft. over broken SW. slope.
81.04	The cor. of secs. 16, 17, 20, and 21.