

# County Surveyor's Record, Douglas County, Oregon

16887

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R 3 W., Willamette Mer., Oregon

CHAINS

80.38

The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 29 S R 3 W

S 8	S 9
S 17	S 16

1966

from which the remains of an original bearing tree

A madrone stump, 33 ins. diam., bears N. 55° E.,  
13 lks. dist., no marks visible on open blaze.

and bearing trees mkd. by Jelley and Roseberry in 1966

A fir, 15 ins. diam., bears N. 77° E., 99 lks.  
dist., with healed blaze.

A madrone, 21 ins. diam., bears S. 55° E., 111 lks.  
dist., with scribe marks T29S R3W S16 BT visible  
on bark blaze.

A madrone, 9 ins. diam., bears S. 33° W., 53 lks.  
dist., with scribe marks X BT visible on bark  
blaze.

A cedar, 34 ins. diam., bears N. 4° W., 51 lks.  
dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone,  
dogwood, yew, and alder; undergrowth, salal, vine maple,  
poison oak, Oregon grape, rhododendron, ferns, and  
grasses.

From the cor. of secs. 4, 5, 8, and 9, perpetuated and recorded by Warren Hootman, Registered Land Surveyor, No. 399, in 1961, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 29 S R 3 W

S 5	S 4
S 8	S 9

1966

from which the remains of the original bearing trees

A burned cedar snag, 28 ins. diam., bears S. 80° E.,  
18 lks. dist., no marks visible.

A madrone, 12 ins. diam., bears S. 66° W., 17 1/2 lks.  
dist., remarked by Hootman in 1961, BT S8.

A madrone shell, 24 ins. diam., bears N. 35° W.,  
42 lks. dist., no marks visible.

and bearing trees mkd. by Hootman