

County Surveyor's Record, Douglas County, Oregon

16889

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R 3 W., Willamette Mer., Oregon

CHAINS	
	N 1/16 S 5 S 4 1980
	from which A fir, 5 ins. diam., bears S. 39 3/4° E., 19 1/2 lks. dist., mkd. N 1/16 S4 BT. A fir, 8 ins. diam., bears S. 87 3/4° W., 25 lks. dist., mkd. N 1/16 S5 BT. Descend 10 ft. over NE. slope.
60.50	Creek, 2 lks. wide, course S. 60° E.; asc. 40 ft. over SE. slope.
62.85	Spur, slopes S. 50° E.; desc. 15 ft. over NE. slope.
66.20	Creek, 2 lks. wide, course S. 25° E.; asc. 75 ft. over SW. slope.
69.14	The cor. of secs. 4 and 5 only, on the N. bdy. of the Tp. Land, mountainous. Soil, rocky clay. Timber, oak, fir, madrone, ash, maple, yew, cedar, hemlock, alder, pine, and cherry; undergrowth, fern, poison oak, blackberry, vine maple, huckleberry, arrowwood, hazel, Oregon grape, and young timber.
	From the cor. of secs. 20, 21, 28, and 29. N. 89° 50' W., bet. secs. 20 and 29. Descend 5 ft. over SW. slope, through heavy timber and dense undergrowth.
2.05	Ravine, drains S.; asc. 80 ft. over SE. slope.
9.20	Ridge, bears N. 15° E. and S. 15° W.; desc. 135 ft. over NW. slope.
14.70	Ravine, drains N. 20° W.; asc. 130 ft. over NE. slope.
25.85	Spur, slopes N. 20° E.; desc. 35 ft. over NW. slope.
30.90	Ravine, drains S. 40° E.; asc. 65 ft. over SE. slope.
40.58	The 1/4 sec. cor. of secs. 20 and 29, perpetuated by person(s) unknown, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 2 ins. above ground, from which the remains of an original bearing tree A laurel stump, 14 ins. diam., bears N. 24° E., 38 lks. dist., with fragmentary scribe marks visible on partially healed blaze.
	At the corner point Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.