

County Surveyor's Record, Douglas County, Oregon

16890

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Mer., Oregon

CHAINS

T 29 S R 3 W

1/4 $\frac{S\ 20}{S\ 29}$

1980

from which new bearing trees

A cedar, 7 ins. diam., bears N. 12 1/2° W., 65 lks.
dist., mkd. 1/4 S20 BT.

A fir, 15 ins. diam., bears S. 24 1/2° E., 63 lks.
dist., mkd. 1/4 S29 BT.

Reset iron pipe alongside iron post.

N. 89° 30' W., beginning new measurement.

Ascend 25 ft. over SE. slope.

3.10 Ridge, bears N. 70° E. and S. 50° W.; desc. 235 ft. over
NW. slope.

17.35 Ravine, drains N. 10° W.; asc. 125 ft. over NE. slope.

22.65 Spur, slopes N. 50° E.; desc. 520 ft. over NW. slope.

40.34 The cor. of secs. 19, 20, 29, and 30, perpetuated and
recorded by Edwin S. Woodford, Deputy County Surveyor, in
1953, monumented with an iron pipe, 1 in. diam., firmly
set, projecting 12 ins. above ground, from which the
remains of an original bearing tree

A root hole, bears N. 70° E., 62 lks. dist.,
alongside of which is a fir, 30 ins. diam.,
no marks visible.

and bearing trees mkd. by Woodford

A cedar, 32 ins. diam., bears S. 68° W.,
68 lks. dist., with scribe marks R3W B visible
on partially healed blaze.

A fir stump, 40 ins. diam., bears S. 28° W.,
162 lks. dist., with healed blaze.

A cedar, 30 ins. diam., bears N. 55° W.,
79 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 29 S R 3 W

$\frac{S\ 19\ | S\ 20}{S\ 30\ | S\ 29}$

1980

from which new bearing trees

A fir, 10 ins. diam., bears N. 9° E., 46 1/2 lks.
dist., mkd. T29S R3W S20 BT.

A fir, 10 ins. diam., bears S. 33 1/2° W., 121 lks.
dist., mkd. T29S R3W S30 BT.