

County Surveyor's Record, Douglas County, Oregon

16893

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R 3 W., Willamette Mer., Oregon

CHAINS

N. 89° 44' W., bet. secs. 17 and 20.

Descend 65 ft. over SW. slope, through open field.

1.75 Dirt road, 15 lks. wide, bears N. and S.

2.00 Ravine, drains S.; asc. 115 ft. over SE. slope.

10.95 Spur, slopes S. 15° W.; desc. 80 ft. over SW. slope.

14.60 Ravine, drains S. 10° W.; asc. 30 ft. over SE. slope.

17.25 Spur, slopes S.; desc. 15 ft. over SW. slope.

20.305 Point for the E 1/16 sec. cor. of secs. 17 and 20.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 17}{S\ 20}$

1980

from which

A fir, 13 ins. diam., bears N. 30 1/4° W., 74 lks. dist., mkd. E 1/16 S17 BT.

A pine, 14 ins. diam., bears S. 52 3/4° W., 130 lks. dist., mkd. E 1/16 S20 BT.

Descend 300 ft. over SW. slope.

20.65 Dirt road, 15 lks. wide, bears N. 15° E. and S. 15° W.

37.30 Dirt road, 15 lks. wide, bears N. 20° W. and S. 5° E., in curve.

39.30 Letitia Creek, 15 lks. wide, course S. 10° W.; asc. 5 ft. over E. slope.

40.61 The 1/4 sec. cor. of secs. 17 and 20, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1920, further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1960, monumented with an iron shaft, 1 1/4 ins. x 1 1/4 ins., firmly set, projecting 3 ins. above ground.

from which a bearing tree mkd. by Irving

A yew, 13 ins. diam., bears S. 28 1/2° W., 52 lks. dist., with illegible scribe marks visible on open blaze.

and a bearing tree mkd. by Byron

A cedar, 22 ins. diam., bears N. 61° E., 42 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W

1/4 $\frac{S\ 17}{S\ 20}$

1980