

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 3 W., Willamette Mer., Oregon

16896

CHAINS

COUNTY SURVEYORS OFFICE

T 29 S  
S 7 | S 8  
S 18 | S 17

1962

from which the remaining original bearing tree

A laurel, 30 ins. diam., bears N. 6° E., 27 lks. dist., with illegible scribe marks visible on open blaze. (Record, N. 12° E.)

and bearing trees mkd. by Byron

A grand fir, 10 ins. diam., bears S. 33° E., 19-1/2 lks. dist., with healed blaze.

A cedar, 20 ins. diam., bears S. 80° W., 105 lks. dist., with illegible scribe marks visible on opened blaze.

A fir, 16 ins. diam., bears N. 34° W., 58 lks. dist., with healed blaze.

Land, mountainous

Soil, rocky clay loam.

Timber, fir, hemlock, maple, oak, madrone, cedar, dogwood, yew, chinquapin, and alder; undergrowth, salal, vine maple, poison oak, Oregon grape, rhododendron, ferns and grasses.

N. 88° 13' W., bet. secs. 7 and 18.

Ascend 95 ft. over broken SE. slope, through heavy timber and dense undergrowth

5.70 Ridge, bears N. 20° E. and S. 20° W.; desc. 415 ft. over W. slope, changing to NW. slope.

31.85 Long Wiley Creek, 10 lks. wide, course S.; asc. 120 ft. over E. slope.

39.14 Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2-1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 29 S    R 3 W  
1/4    S 7  
      S 18

1980

from which

A fir, 7 ins. diam., bears N. 51-1/2° E., 32-1/2 lks. dist., mkd. 1/4 S7 BT.

A fir, 11 ins. diam., bears S. 38-1/2° W., 47 lks. dist., mkd. 1/4 S18 BT.

Ascend 225 ft. over E. slope.

46.60 Spur, slopes S. 20° W.; desc. 55 ft. over W. slope.