

# County Surveyor's Record, Douglas County, Oregon

16897

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 3 W., Willamette Mer., Oregon

**CHAINS**

50.15

Ravine, drains S.; asc. 140 ft. over SE. slope.

56.55

Spur, slopes S. 15° W.; desc. 305 ft. over W. slope, changing to SW. slope.

71.20

Short Wiley Creek, 5 lks. wide, course S. 10° W.; asc. 100 ft. over SE. slope.

74.26

The cor. of secs. 7 and 18 only, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 29 S T 29 S

S 12 | S 7  
          | S 18

R 4 W R 3 W  
1964

from which the remains of the original bearing trees

A yew snag, 13 ins. diam., bears N. 47° E., 27 lks. dist., no marks visible.

A yew snag, 14 ins. diam., bears N. 25° W., 9 lks. dist., no marks visible.

and bearing trees mkd. by Beck

A fir, 14 ins. diam., bears N. 34 1/4° E., 40 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears S. 61 1/4° E., 35 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, yew, maple, madrone, cedar, oak, and alder; undergrowth, salal, poison oak, blackberry, thimbleberry, fern, arrowwood, hazel, Oregon grape, dogwood, and young timber.

N. 0° 54' W., bet. secs. 7 and 8.

Ascend 165 ft. over broken SE. slope, through heavy timber and dense undergrowth.

29.10

Ridge, bears N. 20° E. and S. 20° W.; desc. 10 ft. over NW. slope.

32.75

Bottom of descent, slopes W.; asc. 10 ft. over SW. slope.

38.72

The 1/4 sec. cor. of secs. 7 and 8, determined at record bearing and distance from the remains of the original bearing trees

A madrone, 26 ins. diam., bears S. 80° E., 9 lks. dist., with chaining notch and axe marks visible on decayed blaze.

A root hole, bears N. 75° W., 78 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.