

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Mer., Oregon

16898

CHAINS

T 29 S R 3 W

1/4

S 7 | S 8

1980

from which new bearing trees

A fir, 6 ins. diam., bears S. 4° E., 27 1/2 lks.
dist., mkd. 1/4 S8 BT.

A fir, 7 ins. diam., bears N. 42 3/4° W., 44 lks.
dist., mkd. 1/4 S7 BT.

N. 2° 39' E., beginning new measurement.

Ascend 125 ft. over SW. slope.

6.15 Spur, slopes N. 85° W.; desc. 110 ft. over NW. slope.

7.10 Dirt road, 15 lks. wide, bears N. 10° W. and S. 10° E.

21.65 Ridge, bears N. 50° W. and S. 25° E.; desc. 65 ft. over
NE. slope.

33.55 Bottom of descent, slopes S. 75° E.; asc. 85 ft. over
SE. slope.

39.30 Spur, slopes S. 70° E.; desc. 80 ft. over NE. slope.

43.63 The cor. of secs. 5, 6, 7, and 8, perpetuated and
recorded by Karen Reed, Deputy County Surveyor, in 1979,
monumented with an iron post, 1 1/4 ins. diam., firmly set,
projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S

S 6 | S 5

S 7 | S 8

R 3 W

1979

from which the remains of an original bearing tree

A fir snag, 40 ins. diam., bears S. 87° E.,
28 lks. dist., with illegible scribe marks
visible on bark.

and bearing trees mkd. by Reed

A fir, 8 ins. diam., bears N. 72° E., 67 lks.
dist., with scribe marks T29S R3W S5 CS BT
visible on open double blaze.

A cedar, 18 ins. diam., bears S. 46 1/4° E., 12 lks.
dist., with scribe marks T29S R3W S8 CS BT
visible on open double blaze.

A fir, 8 ins. diam., bears N. 75° W., 23 lks.
dist., with scribe marks T29S R3W S6 CS BT
visible on open double blaze.

A fir, 5 ins. diam., bears N. 24° W., 37 lks.
dist., with scribe marks T29S R3W S6 CS BT
visible on open double blaze.