

County Surveyor's Record, Douglas County, Oregon

16901

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Mer., Oregon

CHAINS

A fir stump, 30 ins. diam., bears N. 40° E.,
46 lks. dist., with scribe mark 2 visible on
opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 29 S	T 29 S
R 4 W	S 6
S 1	S 7
	R 3 W

1980

from which new bearing trees

A grand fir, 8 ins. diam., bears N. 31 3/4° E.,
102 lks. dist., mkd. T29S R3W S6 BT.

A grand fir, 9 ins. diam., bears S. 29 1/2° E.,
58 lks. dist., mkd. T29S R3W S7 BT.

Land, mountainous.

Soil, rocky clay.

Timber, yew, oak, maple, fir, hemlock, cedar, madrone,
and alder; undergrowth, blackberry, poison oak, hazel,
arrowwood, vine maple, fern, thimbleberry, Oregon grape,
and young timber.

N. 1° 29' E., bet. secs. 5 and 6.

Descend 135 ft. over NE. slope, through heavy timber and
dense undergrowth.

6.05 Creek, 2 lks. wide, course N. 85° E.; asc. 210 ft. over
SE. slope.

8.90 Dirt road, 20 lks. wide, bears S. 80° E. and S. 50° W.,
in curve.

17.15 Spur, slopes S. 85° E.; desc. 435 ft. over NE. slope.

24.85 Creek, 2 lks. wide, course E.; asc. 120 ft. over
SE. slope.

30.70 Spur, slopes S. 75° E.; desc. 60 ft. over NE. slope.

36.64 Point for the 1/4 sec. cor. of secs. 5 and 6, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 29 S	R 3 W
	1/4
S 6	S 5
	1980

from which

A cedar, 4 ins. diam., bears S. 60 3/4° E., 9 1/2 lks.
dist., mkd. X BT.