


County Surveyor's Record, Douglas County, Oregon

16903

Dependent Resurvey, Portion of Donation Land Claim No. 37,
Tps. 29 S., Rs. 3 and 4 W., Willamette Mer., Oregon

CHAINS

- 104.74 Ascend 45 ft. over SE. slope.
 - 114.80 Intersect the line bet. secs. 19 and 24, Tps. 29 S.,
Rs. 3 and 4 W., S. 0° 41' W., 0.01 chs. dist., from the
1/4 sec. cor. of sec. 24 only.
 - 119.07 Ridge, bears N. 25° E. and S. 25° W.; desc. 80 ft. over
broken SW. slope.
- The crossing closing corner, at intersection with the N. and S. center line of the NE 1/4 of sec. 24 and the N. bdy. of Claim No. 37, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.



from which bearing trees mkd. by Jelley and Roseberry

A fir, 11 ins. diam., bears N. 17° E., 41 lks. dist., with fragmentary scribe marks visible on open blaze.


A cedar, 18 ins. diam., bears N. 51° W., 32 1/2 lks. dist., with scribe marks T29S R4W S24 CCC BT visible on open blaze.

From this point, a cor. established and recorded by Edwin S. Woodford, Registered Engineer, No. 622, in 1956, bears N. 55° 30' W., 0.095 chs. dist., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 2 ins. above ground, from which bearing trees mkd. by Woodford

A cedar, 13 ins. diam., bears S. 40 1/4° W., 8 1/2 lks. dist., with fragmentary scribe marks visible on open blaze.

A cedar, 18 ins. diam., bears S. 84° W., 27 lks. dist., with healed blaze.

- 123.10 From this same point, the center E 1/16 sec. cor. of sec. 24, bears S. 5° 20' W., 4.425 chs. dist.
Descend 100 ft. over SW slope.
Creek, 3 lks. wide, course S.; asc. 20 ft. over SE slope.
- 123.72 The NW. cor. of Donation Land Claim No. 37, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.



from which bearing trees mkd. by Jelley and Roseberry

A pine, 12 ins. diam., bears S. 81 1/2° E., 97 lks. dist., with scribe marks C37 BT visible on open blaze.