

County Surveyor's Record, Douglas County, Oregon

16906

Subdivision of Sec. 21,
T. 29 S., R. 3 W., Willamette Mer., Oregon

CHAINS	
54.40	Creek, 2 lks. wide, course N. 10° W.; desc. 5 ft. over NW. slope.
55.55	Creek, 10 lks. wide, course N. 10° W.; asc. 100 ft. over E. slope.
60.89	Point for the center W 1/16 sec. cor. of sec. 21. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> W 1/16 C ————— C S 21 1980 </div> from which <div style="margin-left: 40px;"> A grand fir, 23 ins. diam., bears N. 43° E., 17 lks. dist., mkd. CW 1/16 S21 BT. A fir, 33 ins. diam., bears S. 6 1/4° W., 24 lks. dist., mkd. CW 1/16 S21 BT. </div> Ascend 90 ft. over NE. slope.
64.80	Spur, slopes N. 30° E.; desc. 255 ft. over NW. slope.
74.80	Creek, 2 lks. wide, course N. 15° E.; asc. 30 ft. over NE. slope.
77.40	Spur, slopes N. 20° E.; desc. 60 ft. over NW. slope.
81.19	The 1/4 sec. cor. of secs. 20 and 21.
9.05	From the center W 1/16 sec. cor. of sec. 21. N. 0° 16' W., on the N. and S. center line of the NW 1/4 of sec. 21. Descend 190 ft. over NE. slope. Dirt road, 20 lks. wide, bears N. 45° W. and S. 45° E.
11.80	Creek, 5 lks. wide, course N. 50° W.; asc. 15 ft. over SW. slope.
12.20	Spur, slopes N. 25° W.; desc. 55 ft. over NE. slope.
20.09	Point for the NW 1/16 sec. cor. of sec. 21, at intersection with the E. and W. center line of the NW 1/4. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> NW 1/16 S 21 1980 </div> from which <div style="margin-left: 40px;"> A cedar, 15 ins. diam., bears S. 10° W., 117 lks. dist., mkd. NW 1/16 S21 BT. A fir, 18 ins. diam., bears N. 20° W., 293 lks. dist., mkd. NW 1/16 S21 BT. </div>