

County Surveyor's Record, Douglas County, Oregon

16911

T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

error. Only lines bounding or crossing public lands were blazed.

The geographic position of the W 1/16 section corner of section 3 only, on the south boundary of the section, as determined by a tie to horizontal control station "ANT", established by Douglas County in 1974, located in the SW 1/4 of section 3, is as follows:

Latitude 43° 14' 35.8" N. Longitude 122° 55' 33.1" W.

The mean magnetic declination is 19° 30' E.

Dependent Resurvey of a Portion of the West Boundary,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

(Restoring the survey by Samuel C. Flint in 1882
and the remonumentation by Harold D. Corbin in 1958)

Beginning at the cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., perpetuated and recorded by Thomas E. Shrum, Jr., Logging Engineer, No. 4287, in 1961, determined at record bearing and distance from the remains of the original bearing trees

A root hole, bears S. 58° E., 59 lks. dist.,
with down fir alongside, 40 ins. diam., with
scribe marks T27S R W S18 BT visible on bark.

A root hole, bears S. 60° W., 7 lks. dist.

A root hole, bears N. 42° W., 58 lks. dist.

and bearing trees marked by Shrum

A root hole, bears N. 1° E., 69 lks. dist.,
with down hemlock alongside, 14 ins. diam.,
with illegible scribe marks visible on
partially healed blaze.

A fir, 17 ins diam., bears S. 71 1/2° E., 54 lks.
dist., with healed blaze and scribe marks BT
visible on bark at base.

A root hole, bears S. 35 1/2° W., 124 lks. dist.,
with down fir alongside, 30 ins. diam., no marks
visible.

A cedar stump, 14 ins. diam., bears N. 23° W.,
69 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

FDOR PER DEGR00T
M 109-79 4-90

T 27 S

R 3 W R 2 W

S 12 | S 7

S 13 | S 18

1979

from which new bearing trees