

County Surveyor's Record, Douglas County, Oregon

16912

Dependent Resurvey, Portion of W. Bdy.,
T 27 S R 2 W Willamette Meridian, Oregon

CHAINS	
	<p>A cedar, 9 ins. diam., bears N. 17° E., 23 lks. dist., mkd. T27S R2W S7 BT.</p> <p>A hemlock, 5 ins. diam., bears S. 31° W., 43 lks. dist., mkd. T27S R3W S13 BT.</p> <p>A hemlock, 6 ins. diam., bears N. 66° W., 46 lks. dist., mkd. T27S R3W S12 BT.</p> <p>The cor. is located in the SE. cor. of a logged area.</p> <p>N. 1° 47' E., bet. secs. 7 and 12, marking and blazing the true line.</p> <p>Descend 160 ft. over NW. slope, along E. edge of logged area.</p>
12.85	<p>Spur, slopes N. 25° W.; desc. 160 ft. over broken N. slope.</p>
19.88	<p>The S 1/16 sec. cor. of secs. 7 and 12, established and recorded by Thomas E. Shrum, Jr., Logging Engineer, No. 4287, in 1961, and is accepted as the corner, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 10 ins. above ground, from which the bearing tree mkd. by Shrum</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears S. 29° W., 17 lks. dist., with scribe marks 1/16 S12 HE 4287 BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: right; margin-right: 100px;"> <p>FD OK PER DEEBOOT M 109-79 4-90</p> </div> <div style="text-align: center; margin-right: 100px;"> <p>S 1/16</p> <p>S 12 S 7</p> <p>1979</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A yew, 14 ins. diam., bears S. 44° E., 37 lks. dist., mkd. S 1/16 S7 BT.</p> <p>The cor. is located in the NE. cor. of logged area.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 47' E., beginning new measurement.</p> <p>Descend 265 ft. over broken N. slope, through moderate timber and undergrowth.</p>
14.65	<p>Foot of hill, bears E. and W.; desc. slightly over nearly level land.</p>
16.60	<p>Power line, bears E. and W.</p>
17.50	<p>Wire fence, extends N. 35° W. and S. 35° E.</p>
17.80	<p>Gravelled road, 15 lks. wide, bears N. 35° W. and S. 35° E.</p>
19.88	<p>The 1/4 sec. cor. of secs. 7 and 12, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p>