

County Surveyor's Record, Douglas County, Oregon

16913

Dependent Resurvey, Portion of W. Bdy.,
T. 27 W., R. 2 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 27 S

R	3	1/4	S	12		S	7	2	R
W									W
1968									

from which the remains of an original bearing tree

A fir stump, 28 ins. diam., bears N. 15° W.,
8 lks. dist., no marks visible.

and bearing trees mkd. by Tracy

A fir, 13 ins. diam., bears S. 13° E., 31 1/2 lks.
dist., with healed blaze.

A fir, 15 ins. diam., bears S. 55 1/2° W., 39 lks.
dist., with healed blaze.

N. 0° 24' W., beginning new measurement.

Descend 15 ft. over NE. slope, through light timber and moderate undergrowth.

0.85 Left bank of Little River, bears N. 45° W. and S. 45° E.,
course N. 45° W.

2.10 Right bank of little River, bears N. 45° W. and S. 45° E.;
asc. 295 ft. over SW. slope.

3.60 Little River Road, asphalt surface, 40 lks. wide, bears
N. 45° W. and S. 45° E.

4.15 Power line, bears N. 45° W. and S. 45° E.

19.90 The N 1/16 sec. cor. of secs. 7 and 12, established and
'recorded by Thomas E. Shrum, Jr., Logging Engineer, No.
4287, in 1961, and is accepted as the corner, monumented
with an iron rod, 5/8 in. diam., firmly set, projecting
12 ins. above ground, from which a bearing tree mkd. by
Shrum

A sugar pine, 11 ins. diam., bears N. 69° E.,
45 lks. dist., with scribe marks S7 BT visible
on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, directly over the iron rod, with brass cap mkd.

N 1/16				
S	12		S	7
1979				

from which a new bearing tree

A grand fir, 5 ins. diam., bears N. 22 1/2° W.,
29 lks. dist., mkd. X BT.

Cor. is located in E. edge of logged area, edge bears N.
and S.