

# County Surveyor's Record, Douglas County, Oregon

16914

Dependent Resurvey, Portion of W. Bdy.,  
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

N. 0° 24' W., beginning new measurement.

Ascend 60 ft. over SW. slope, along E. edge of logged area.

2.50 Spur, slopes S. 70° W.; desc. 20 ft. over NW. slope.

5.60 Enter moderate timber and undergrowth, edge bears S. and W.

7.90 Creek, 3 lks. wide, course S. 50° W.; asc. 150 ft. over SE. slope.

18.80 Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.

19.90 Cor. of secs. 1, 6, 7, and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

T 27 S

R 3 W	R 2 W
S 1	S 6
S 12	S 7

1958

from which the remains of bearing trees mkd. by Corbin in 1958

A sawed fir stump, 20 ins. diam., bears N. 40° E., 155 lks. dist., with healed blaze.

A fir, 11 ins. diam., bears S. 55° E., 95 lks. dist., with healed blaze. (Record, S. 57° E., 87 lks.)

A fir, 20 ins. diam., bears S. 60° W., 36 lks. dist., with healed blaze.

and new bearing trees

A fir, 10 ins. diam., bears N. 15° E., 137 lks. dist., mkd. T27S R2W S6 BT.

A pine, 33 ins. diam., bears N. 15° W., 61 lks. dist., mkd. T27S R3W S1 BT.

Dependent Resurvey of  
a Portion of the Subdivisional Lines,  
T. 27 S., R. 2 W., Willamette Meridian, Oregon

(Restoring the survey by Samuel C. Flint in 1882, and the retracement and survey by Charles E. Roberts in 1905-07)

From the cor. of secs. 1, 2, 11, and 12, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, further perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, with brass cap mkd.