

County Surveyor's Record, Douglas County, Oregon

16915

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

FDOC 4/84
 BY GEISLER
 M 90-55

T 27 S

S 2	S 1
S 11	S 12

 R 2 W
 1962

from which the remains of an original bearing tree

A cedar root crown, bears N. 20° W., 24 lks.
dist., with a downed cedar alongside, 36 ins.
diam., no marks visible.

and bearing trees mkd. by Roberts in 1905-07

A fir, 32 ins. diam., bears S. 76° E., 46 lks.
dist., with healed blaze. (Record, S. 79° E.)

A fir, 28 ins. diam., bears S. 39° W., 54 lks.
dist., with healed blaze.

and bearing trees mkd. by Tracy in 1968

A yew, 8 ins. diam., bears N. 36° E., 41 lks.
dist., with scribe marks T27S R2W S1 CS BT
visible on open blaze.

A grand fir, 21 ins. diam., bears S. 15° E.,
47 lks. dist., with healed blaze.

A fir, 22 ins. diam., bears N. 6° W., 18 lks.
dist., with healed blaze.

The cor. is located in NW. cor. of logged area, edge
bears E. and S. 40° W.

N. 0° 19' W., bet. secs. 1 and 2, marking and blazing the
true line.

Descend 10 ft. over NE. slope, through heavy timber and
dense undergrowth.

0.20 Creek, 2 lks. wide, course N. 65° W.; desc. 175 ft. over
NE. slope.

2.90 Gravelled road, 20 lks. wide, bears N. 70° W. and
S. 70° E.

16.00 Creek, 4 lks. wide, course N. 50° E.; desc. 30 ft. over
NE. slope.

22.55 Left bank of Little River, bears N. 70° W. and S. 70° E.,
course N. 70° W.

23.20 Right bank of Little River, bears N. 70° W. and S. 70° E.;
asc. 680 ft. over SW slope.

24.60 Power line, bears N. 80° W. and S. 80° E.

24.90 Little River Road, asphalt surface, 40 lks. wide, bears
N. 70° W. and S. 70° E.

39.20 Point for the 1/4 sec. cor. of secs. 1 and 2, at propor-
tionate distance; there is no remaining evidence of the
original cor.