

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

16916

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 27 S R 2 W

1/4

S 2 | S 1

1979

*FD. OK 4/84
BY GEISLER
M 90-55
CS 6/14 6/06*

from which

A fir, 18 ins. diam., bears S. 29° E., 30 lks. dist., mkd. 1/4 S1 BT.

A fir, 13 ins. diam., bears S. 58 1/2° W., 19 1/2 lks. dist., mkd. 1/4 S2 BT.

Ascend 265 ft. over SW. slope.

52.00 Ridge, bears N. 80° W. and S. 80° E.; desc. 405 ft. over steep N. slope.

55.45 Enter logged area, edge bears N. and S. 45° E.

58.80 Point for the N 1/16 sec. cor. of secs. 1 and 2.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16

S 2 | S 1

1979

from which

A sawed fir stump, 18 ins. diam., bears N. 60° E., 15 lks. dist., mkd. N 1/16 S1 BT.

A fir, 6 ins. diam., bears S. 58 1/2° W., 40 lks. dist., mkd. N 1/16 S2 BT.

*FD. OK 7/84
BY GEISLER
M 90-55*

Cor. is located in W. edge of logged area, edge bears N. and S.

Descend 430 ft. over steep N. slope.

63.05 Enter timber, edge bears N. 30° E. and S.

67.30 Emile Creek, 40 lks. wide, course N. 85° W.; asc. 250 ft. over SE. slope.

74.05 Gravelled road, 20 lks. wide, bears E. and W.

79.53 The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1967, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 26 S
S 35 | S 36 R

S 2 | S 1 W
1967