

# County Surveyor's Record, Douglas County, Oregon

16917

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 27 S., R 2 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A root hole, bears S. 70° E., 30 lks. dist.

A fir, 22 ins. diam., bears S. 30° W., 24 lks. dist., with illegible scribe marks visible on opened blaze.

A sawed fir stump, 35 ins. diam., bears N. 14° W., 14 lks. dist., no scribe marks visible on axe blaze.

and a bearing trees mkd. by Collier in 1913

A fir, 18 ins. diam., bears N. 39° 30' E., 18 lks. dist., with illegible scribe marks visible on opened blaze.

and bearing trees mkd. by Tracy in 1967

A fir, 15 ins. diam., bears N. 4° E., 8 lks. dist., with healed blaze.

A fir, 18 ins. diam., bears S. 84° E., 136 lks. dist., with healed blaze.

A fir, 22 ins. diam., bears S. 13° W., 30 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, maple, pine, ash, oak, alder, willow, dogwood, madrone, chinquapin, hemlock, and yew; undergrowth, fern, salal, poison oak, huckleberry, wild rose, blackcap, Oregon grape, vine maple, hazel, arrowwood, thimbleberry, salmonberry, manzanita, canyon live oak, and young timber.

From the 1/4 sec. cor. of secs. 6 and 7, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 27 S

1/4  $\frac{S\ 6}{S\ 7}$

R 2 W

1968

from which the remains of the original bearing trees

A root hole, bears South, 5 lks. dist., with down fir alongside, size indeterminate, no marks visible.

A fir, 45 ins. diam., bears N. 40° W., 35 lks. dist., with scribe marks 1/4 S BT visible on bark.

and a bearing tree mkd. by Tracy

A fir, 18 ins. diam., bears N. 81° W., 90 lks. dist., with healed double blaze.