

County Surveyor's Record, Douglas County, Oregon

16919

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which bearing trees mkd. by Roberts in 1905-07</p> <p style="padding-left: 40px;">A fir, 54 ins. diam., bears S. 65° E., 137 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 42 ins. diam., bears S. 23 1/2° W., 154 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 31° W., 107 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Tracy</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 50° E., 12 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 2° E., 36 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 78° W., 14 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 60° W., 17 lks. dist., with healed blaze.</p> <p>and a reference monument set by Tracy</p> <p style="padding-left: 40px;">An iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, and in a mound of stone, 3 ft. base to top, bears West, 0.015 chs. dist., with brass cap mkd. T27S R2W S5 S6 S7 S8 1968.</p> <p>N. 2° 06' E., bet. secs. 5 and 6.</p> <p>Ascend 140 ft. over SW. slope, through heavy timber and dense undergrowth.</p>
9.30	Spur, slopes S. 50° E.; desc. 270 ft. over NE. slope.
20.68	<p>Point for the S 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 6 S 5 1979</p>
	<p>from which</p> <p style="padding-left: 40px;">A hemlock, 20 ins. diam., bears S. 33° E., 45 1/2 lks. dist., mkd. S 1/16 S5 BT.</p> <p style="padding-left: 40px;">A yew, 13 ins. diam., bears S. 86° W., 20 lks. dist., mkd. S 1/16 S6 BT.</p> <p>Descend 235 ft. over NE. slope.</p>
24.00	Top of rock bluff, 30 ft. high, edge bears N. 60° W. and S. 60° E.
26.95	Creek, 5 lks. wide, course S. 50° E.; asc. 495 ft. over SW. slope.
36.95	SW. cor. of logged area, edge bears N. and E.