

# County Surveyor's Record, Douglas County, Oregon

16920

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

41.36

The 1/4 sec. cor. of secs. 5 and 6, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1969, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 27 S R 2 W  
1/4 S 6 | S 5  
1969

from which the remains of the original bearing trees

A root hole, bears S. 60° E., 22 lks. dist., with sawed fir stump alongside, 38 ins. diam., no marks visible.

A fir, 45 ins. diam., bears S. 80° W., 53 lks. dist., with scribe marks 1/4 S BT visible on bark. (Record, 52 lks.)

and the remains of the bearing trees mkd. by Tracy

A root hole, bears N. 49° E., 40 lks. dist., with down pine, 12 ins. diam., alongside, with healed double blaze.

A fir, 10 ins. diam., bears N. 51 1/2° W., 9 1/2 lks. dist., with scribe mark S visible on partially healed blaze.

and a new bearing tree

A fir, 5 ins. diam., bears S. 68 1/2° E., 164 lks. dist., mkd. 1/4 S5 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, yew, hemlock, cedar, maple, and dogwood; undergrowth, hazel, arrowwood, fern, Oregon grape, huckleberry, blackberry, vine maple, and young timber.

Subdivision of Section 3,  
T. 27 S., R. 2 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of sec. 3 only, on the S. bdy. of the sec., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 27 S R 2 W  
1/4 S 3  
1957 1978

from which a bearing tree mkd. by Corbin in 1957, and rescribed by Vernon R. Tracy, Deputy County Surveyor, in 1968

A fir, 15 ins. diam., bears N. 42 3/4° W., 61 1/2 lks. dist., with scribe marks 1/4 S3 BT visible on open blaze.