

# County Surveyor's Record, Douglas County, Oregon

16921

Subdivision of Section 3,  
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	<p>and the remains of a bearing tree mkd. by Tracy in 1968</p> <p style="padding-left: 40px;">A root hole, bears N. 2° E., 97 lks. dist., with down hemlock alongside, 10 ins. diam., with scribe marks 1/4 S3 CS BT.</p> <p>and a bearing tree mkd. by Jelley in 1978</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 47 1/4° E., 72 1/2 lks. dist., with scribe marks 1/4 S3 BT visible on open blaze.</p> <p>N. 0° 49' E., on the N. and S. center line of sec. 3.</p> <p>Descend 160 ft. over NW. slope, through light timber and dense undergrowth.</p>
10.50	Creek, 5 lks. wide, course N. 65° E.; asc. 20 ft. over SE. slope.
13.80	Spur, slopes N. 60° E.; desc. 55 ft. over NE. slope.
20.64	Point for the center S 1/16 sec. cor. of sec. 3.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <pre>           C             S 1/16     S 3                       C                     1979             </pre> </div> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 15 ins. diam., bears S. 35 1/2° E., 4 lks. dist., mkd. C S 1/16 S3 BT.</p> <p style="padding-left: 40px;">A hemlock, 8 ins. diam., bears S. 89° W., 28 lks. dist., mkd. C S 1/16 S3 BT.</p> <p>Descend 60 ft. over NE. slope.</p>
21.70	Left bank of Little River, bears N. 35° W. and S. 35° E., course N. 35° W.
23.10	Right bank of Little River, bears N. 35° W., and S. 35° E.; asc. 215 ft. over SE. slope.
26.60	Little River Road, asphalt surface, 40 lks. wide, bears N. 50° W. and S. 50° E.
27.10	Power line, bears N. 55° W. and S. 55° E.
27.20	Wire fence extends N. 50° W. and S. 50° E.; enter pasture land.
34.30	Leave pasture land, edge bears N. 70° E. and S. 70° W.; enter moderate timber and undergrowth.
41.15	Woven wire fence, extends E. and W.
41.28	Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line.
	<p>Set an iron post, 28 ins. long, 2 1/2 in. diam., 24 ins. in the ground, with brass cap mkd.</p>