

# County Surveyor's Record, Douglas County, Oregon

16922

Subdivision of Section 3,  
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

T 27 S R 2 W  
C 1/4 S 3  
1979

FD. OK BY K DEGROOT  
8/2007 2007-0117

from which

A cedar, 13 ins. diam., bears S. 55 1/2° W.,  
12 1/2 lks. dist., mkd. C 1/4 S3 BT.

A fir, 13 ins. diam., bears N. 70 1/2° W.,  
12 lks. dist., mkd. C 1/4 S3 BT.

Ascend 585 ft. over SE. slope.

49.70 Slope changes to SW.

66.00 Spur, slopes S. 40° W.; asc. 420 ft. over SW. slope.

78.59 The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the  
Tp., monumented with an iron post, 2 1/2 ins. diam., loosely  
set, projecting 18 ins. above ground, with brass cap mkd.

T 26 S R 2 W  
1/4  $\frac{S\ 34}{S\ 3}$   
T 27 S  
1957

from which the original bearing trees

A fir, 55 ins. diam., bears S. 10° W., 30 lks.  
dist., with healed blaze.

A fir, 46 ins. diam., bears N. 10° W., 15 lks.  
dist., with healed blaze.

and bearing trees mkd. by Corbin in 1957

A madrone, 15 ins. diam., bears N. 49 1/2° E., 66 lks.  
dist., with healed blaze.

A fir, 55 ins. diam., bears S. 23 1/4° W., 77 lks.  
dist., with healed blaze. (Record, S. 23 1/2° W.)

Raise a mound of stone, 5 ft. base, 2 ft. high, around  
iron post.

From the 1/4 sec. cor. of secs. 2 and 3, perpetuated and  
recorded by Vernon R. Tracy, Deputy County Surveyor, in  
1968, monumented with an iron post, 2 1/2 ins. diam., firmly  
set, projecting 4 ins. above ground, with brass cap mkd.

T 27 S R 2 W  
1/4  
S 3 | S 2  
1957

from which bearing trees mkd. by Corbin in 1957

A cedar, 15 ins. diam., bears N. 86° E., 55 lks.  
dist., with healed blaze.