

County Surveyor's Record, Douglas County, Oregon

16924

Subdivision of Section 3,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

| CHAINS | | | | | |
|--------|--|-----|-----|------|--|
| | <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears S. 28° E., 19 lks. dist., with scribe marks 1/ S S BT visible on double bark blaze.</p> <p style="margin-left: 40px;">A sawed fir stump, 42 ins. diam., bears N. 35° W., 65 lks. dist., with illegible scribe marks visible on opened blaze.</p> <p>and bearing trees mkd. by Corbin in 1957</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears N. 52° E., 43 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears S. 81° W., 48 lks. dist., with healed blaze.</p> | | | | |
| | <p>From the S 1/16 sec. cor. of secs. 2 and 3, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 1/16</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td colspan="2" style="text-align: center; padding-top: 5px;">1957</td> </tr> </table> </div> <p>from which bearing trees mkd. by Corbin in 1957</p> <p style="margin-left: 40px;">A cedar, 20 ins. diam., bears S. 37° E., 49 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 61 ins. diam., bears S. 66 1/2° W., 101 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Tracy</p> <p style="margin-left: 40px;">A grand fir, 11 ins. diam., bears N. 64 1/2° W., 50 lks. dist., with healed double blaze.</p> <p>N. 89° 02' W., on the E. and W. center line of the SE 1/4 of sec. 3.</p> <p>Ascend 30 ft. over NE. slope.</p> <p>6.60 Spur, slopes N. 20° W.; desc. 235 ft. over NW. slope.</p> <p>35.95 Left bank of Little River, bears N. 70° E. and S. 70° W., course S. 70° W.</p> <p>37.50 Left bank of Little River, bears N. 55° W. and S. 55° E.; asc. 55 ft. over NE. slope.</p> <p>40.24 The center S 1/16 sec. cor. of sec. 3.</p> | S 3 | S 2 | 1957 | |
| S 3 | S 2 | | | | |
| 1957 | | | | | |
| | <p>From the W 1/16 sec. cor. of sec. 3 only, on the S. bdy. of the sec., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd.</p> | | | | |