

County Surveyor's Record, Douglas County, Oregon

16925

Subdivision of Section 3,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

W 1/16 S 3

1978

1957

from which the remains of the bearing trees mkd. by Corbin in 1957

A fir snag, 6 ins. diam., bears N. 45 3/4° W.,
31 lks. dist., with healed blaze.

A fir, 25 ins. diam., bears N. 6 1/2° W.,
48 lks. dist., with healed blaze.

and a bearing tree mkd. by Jelley in 1978

A fir, 6 ins. diam., bears N. 52 1/4° E., 58 lks.
dist., with scribe marks W 1/16 S3 BT visible
on open blaze.

N. 1° 02' E., on the N. and S. center line of the SW 1/4 of sec. 3.

Descend 70 ft. over NW. slope, through moderate timber and undergrowth.

6.45 Creek, 2 lks. wide, course S. 70° W.; asc. 80 ft. over SW slope.

11.70 From this point, the west corner of a fenced enclosure, 1.00 ch. square, bears East, 15 lks. dist., with fences extending N. 50° E. and S. 40° E.

14.25 Gravelled road, 25 lks. wide, bears N. 60° W. and S. 60° E.

16.90 Spur, slopes W.; desc. 55 ft. over NW. slope.

21.37 Point for the SW 1/16 sec. cor. of sec. 3, at intersection with the E. and W. center line of the SW 1/4.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SW 1/16 S 3

1979

from which

A fir, 10 ins. diam., bears S. 47 1/2° E., 48 lks.
dist., mkd. SW 1/16 S3 BT.

A fir, 5 ins. diam., bears N. 51° W., 25 lks.
dist., mkd. SW 1/16 S3 BT.

Set a 5 ft. steel fence post alongside the iron post.

From this point, Douglas County horizontal control station "ANT", bears N. 2° 48' W., 7.56 chs. dist., monumented with a brass tablet, 2 1/2 ins. diam., seated in drill hole in the NE. cor. of a concrete bridge across Little River, mkd. COUNTY SURVEYORS OFFICE ANT 1974.

Descend 45 ft. over NW. slope.

27.00 Left bank of Little River, bears E. and W., course W.