


County Surveyor's Record, Douglas County, Oregon

16927

Subdivision of Section 3,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS



from which a bearing tree mkd. by Corbin in 1957

A hemlock, 12 ins. diam., bears N. 85° E., 51 lks. dist., with healed blaze.

and a bearing tree mkd. by Jelley in 1978

A hemlock, 6 ins. diam., bears N. 32° W., 5 lks. dist., with scribe marks S 1/16 S4 BT visible on open blaze.

Subdivision of Section 6,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 6 and 7.

N. 1° 24' E., on the N. and S. center line of sec. 6.


Ascend 690 ft. over steep SE. slope, through heavy timber and dense undergrowth.

7.00 Foot of rock outcrop, 40 ft. high, 1 ch. wide, edge bears E. and W.

16.10 Spur, slopes S. 65° E.; desc. 100 ft. over NE. slope.

19.86 Point for the center S 1/16 sec. cor. of sec. 6.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



from which

A fir, 20 ins. diam., bears N. 65 1/4° E., 43 lks. dist., mkd. C S 1/16 S6 BT.

A fir, 14 ins. diam., bears S. 42 1/2° W., 34 lks. dist., mkd. C S 1/16 S6 BT.

Descend 10 ft. over NE. slope.

20.30 Ravine, drains S. 65° E.; asc. 300 ft. over SW slope.

39.72 Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.