

County Surveyor's Record, Douglas County, Oregon

16928

Subdivision of Section 6,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	T 27 S R 2 W C 1/4 S 6 1979
	from which
	A grand fir, 6 ins. diam., bears S. 76° E., 9 lks. dist., mkd. C 1/4 S 6 BT.
	A fir, 9 ind. diam., bears S. 11° W., 19 lks. dist., mkd. C 1/4 S6 BT.
	Cor. is located on spur, slopes S. 50° E:
	Descend 415 ft. over NE. slope.
57.30	Creek, 10 lks. wide, course S. 60° E.; asc. 360 ft. over SW. slope.
69.65	Spur, slopes S. 60° E.; desc. 15 ft. over NE slope.
77.70	The 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., perpetuated and recorded by Vernon R. Tracey, Deputy County Surveyor, in 1967, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T 26 S 1/4 $\frac{S\ 31}{S\ 6}$ R 2 W T 27 S 1967
	from which the remains of the original bearing trees
	A fir, 30 ins. diam., bears N. 78° E., 75 lks. dist., with healed blaze. (Record, N.75° E.)
	A fir stump, 34 ins. diam., bears S. 9 1/2° E., 40 lks. dist., with illegible scribe marks visible on opened blaze. (Record, S. 12° E.)
	and bearing trees mkd. by Tracy
	A cedar, 11 ins. diam., bears N. 20 1/2° E., 45 lks. dist., with scribe marks S31 CS BT visible on partially healed double blaze.
	A cedar, 18 ins. diam., bears S. 86 1/2° E., 127 lks. dist., with illegible scribe marks visible on partially healed double blaze.
	From the 1/4 sec. cor. of secs. 5 and 6.
	S. 88° 37' W., on the E. and W. center line of sec. 6.
	Descend 360 ft. over steep SW. slope, through heavy timber and dense undergrowth.
15.25	Creek, 5 lks. wide, course S. 10° E.; desc. 5 ft. over SW. slope.