

County Surveyor's Record, Douglas County, Oregon

16929

Subdivision of Section 6,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

- 16.20 Creek, 5 lks. wide, course S. 50° E.; asc. 705 ft. over NE. slope.
- 39.00 The center 1/4 sec. cor. of sec. 6.
Ascend slightly over NE. slope.
- 39.10 Spur, slopes S. 50° E.; desc. 725 ft. over SW. slope.
- 68.35 Gravelled road, 15 lks. wide, bears N. 15° W. and S. 15° E.
- 77.32 The 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 27 S
1/4
R 3 W | R 2 W
S 1 | S 6
1958

from which an original bearing tree

A fir, 58 ins. diam., bears N. 35° E., 42 lks. dist., with scribe marks 1/4 S BT visible on bark.

and bearing trees mkd. by Corbin in 1958

A fir, 25 ins. diam., bears S. 62° E., 36 lks. dist., with healed blaze.

A cedar, 15 ins. diam., bears S. 51° W., 45 lks. dist., with healed blaze.

From the S 1/16 sec. cor. of secs. 5 and 6.

S. 89° 48' W., on the E. and W. center line of the SE 1/4 of sec. 6.

Ascend 380 ft. over NE. slope, through heavy timber and dense undergrowth.

- 10.95 Spur, slopes S. 25° E.; desc. 80 ft. over SW. slope.

- 37.70 Ravine, drains S. 65° E.; asc. 35 ft. over NE. slope.

- 38.73 The center S 1/16 sec. cor. of sec. 6.

Subdivision of Section 7,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of sec. 7 only, on the S. bdy. of the sec., perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1969, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.

FD OK PER
DEGRROOT
M.103-79 4-90

COUNTY SURVEYORS OFFICE
T 27 S R 2 W
1/4 S 7

1969