

County Surveyor's Record, Douglas County, Oregon

16931

Subdivision of Section 7,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS 41.60	<p>Point for the center 1/4 sec. cor. of sec. 7 determined at the intersection of lines parallel to the N. half mile of the W. bdy. of sec. 7, and the W. half mile of the N. bdy. of sec. 7.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p>FDOK PER DEGROOT M109-79 4-90</p> <p style="text-align: center;">T 27 S R 2 W C 1/4 S 7 1979</p> <p>from which</p> <p style="padding-left: 40px;">A grand fir, 5 ins. diam., bears S. 1/2° E., 42 lks. dist., mkd. C 1/4 S7 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 89 1/2° W., 42 lks. dist., mkd. C 1/4 S7 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 24' W., parallel to the W. bdy. of sec. 7, beginning new measurement.</p> <p>Ascend 140 ft. over SE. slope.</p>
9.10	Gravelled road, 20 lks. wide, bears N. 50° W. and S. 50° E.
19.90	<p>Point for the center N. 1/16 sec. cor. of sec. 7.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam. 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C N 1/16 S 7 C</p> <p>1979</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 62 1/2° W., 109 lks. dist., mkd. C N 1/16 S7 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 27° W., 101 lks. dist., mkd. C N 1/16 S7 BT.</p> <p>Ascend 380 ft. over broken SE. slope.</p>
25.55	Enter logged area, edge bears E. and W.
38.25	Gravelled road, 15 lks. wide, bears E. and W.
39.80	The 1/4 sec. cor. of secs. 6 and 7.
<p>From the 1/4 sec. cor. of secs. 7 and 8, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p>	