

County Surveyor's Record, Douglas County, Oregon

16932

Subdivision of Section 7,
T 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 27 S
1/4 S 7 | S 8
R 2 W
1968

from which the remains of the original bearing trees

A fir stump, 36 ins. diam., bears N. 88° E.,
96 lks. dist., with scribe marks 1/4 S8 BT
visible on opened blaze.

A fir, 38 ins. diam., bears N. 20° W.,
67 lks. dist., with healed blaze.

and bearing trees mkd. by Tracy

A fir, 10 ins. diam., bears S. 75° E.,
23 lks. dist., with healed double blaze.

A pine, 20 ins. diam., bears S. 75° W.,
26 lks. dist., with healed double blaze.

N. 88° 10' W., on the E. and W. center line of sec. 7.

Ascend 120 ft. over SE. slope, through heavy timber and
dense undergrowth.

- 5.10 Spur, slopes S. 30° W.; desc. 255 ft. over SW. slope.
- 33.40 Ravine, drains S. 45° W.; asc. 10 ft. over SE. slope.
- 33.50 Gravelled road, 20 lks. wide, bears N. and S.
- 35.80 Spur, slopes S. 55° W.; desc. 65 ft. over NW. slope.
- 37.90 Ravine, drains S. 55° W.; asc. 10 ft. over SE. slope.
- 38.24 The center 1/4 sec. cor. of sec. 7.

S. 87° 39' W., parallel to the N. bdy. of sec. 7,
beginning new measurement.

Ascend 10 ft. over SE. slope.

- 2.10 Spur, slopes S. 30° W.; desc. 60 ft. over SW. slope.
- 18.75 Wire fence extends N. and S.
- 19.75 Point for the center W 1/16 sec. cor. for the NW 1/4 of
sec. 7, as based on the Flint plat of 1882.

Set an iron post, 28 ins. long 2 1/2 ins. diam., 22 ins. in
the ground, with brass cap mkd.

*FD PER DEERROOT
M109-79 A-90*

C — W 1/16 S 7 — C
1979

from which

A fir, 4 ins. diam., bears N. 74 1/2° E., 42 lks.
dist., mkd. C W 1/16 S7 BT.

A fir, 8 ins. diam., bears N. 40° W., 26 lks.
dist., mkd. C W 1/16 S7 BT.