

County Surveyor's Record, Douglas County, Oregon

16333

Subdivision of Section 7,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	Descend 135 ft. over SW. slope.
33.95	Power line, bears N. 45° E. and S. 45° W.
34.95	Power line, bears N. 45° W. and S. 45° E.
35.30	Little River Road, asphalt surface, 40 lks. wide, bears N. 45° W. and S. 45° E.
37.20	Right bank of Little River, bears N. 40° W. and S. 40° E., course N. 40° W.
37.95	Left bank of Little River, bears N. 40° W. and S. 40° E., asc. 15 ft. over NE. slope.
38.71	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.
	From the center S 1/16 sec. cor. of sec. 7.
	S. 89° 00' W., on the E. and W. center line of the SW 1/4 of sec. 7.
	Descend 35 ft. over SW. slope.
3.65	Little River Road, asphalt surface, 40 lks. wide, bears N. 80° E. and S. 80° W.
7.85	Little River Road, asphalt surface, 40 lks. wide, bears N. 60° W. and S. 60° E.
8.45	Power line, bears N. 80° E. and S. 80° W.
10.60	Power line, bears N. 70° W. and S. 70° E.
14.20	Right bank of Little River, bears N. 65° W. and S. 65° E., course N. 65° W.
16.20	Left bank of Little River, bears N. 65° W. and S. 65° E.; asc. 375 ft. over steep NE. slope.
34.90	Spur, slopes N;; desc. 75 ft. over NW. slope.
37.70	Head of ravine, drains N. 20° E.; asc. 10 ft. over NE. slope.
38.14	The S 1/16 sec. cor. of sec. 7 and 12, on the W. bdy. of the Tp.
	From the center W 1/16 sec. cor. of the NW 1/4 of sec. 7.
	N. 0° 24' W., on the N. and S. center line of the NW 1/4 of sec. 7.
	Ascend 255 ft. over SW. slope, through heavy timber and dense undergrowth.
16.60	Slope changes to SE. slope.
18.70	Wire fence extends E. and W.
19.90	Point for the NW 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the NW 1/4.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with brass cap mkd.