

County Surveyor's Record, Douglas County, Oregon

16937

T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary and a portion of the subdivisional lines, and subdivision of section 9, township 26 south, range 2 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

The south boundary of the township was surveyed by Samuel C. Flint, in 1882.

The north and east boundaries of the township, and a portion of the subdivisional lines were surveyed by John A. McQuinn, in 1883.

A portion of the subdivisional lines was surveyed or resurveyed by William N. Gibb, in 1909-10.

The north three miles of the east boundary and the west four miles of the south boundary of the township was resurveyed by Charles M. Collier, in 1913-14. A revision survey was conducted in the south portion of the township by Collier, in 1913, but was cancelled in 1915.

A corrective survey of portions of the subdivisional lines and east boundary, and the east two miles of the south boundary of the township was executed by Fred Mensch, in 1916. In 1918, Mensch made a revision of his 1916 corrective survey in the subdivisional lines.

A portion of the south boundary of the township was dependently resurveyed by Harold D. Corbin, in 1957.

A portion of the subdivisional lines were dependently resurveyed by Irving Zirpel, Jr. and William W. Glenn, in 1959, and sections 15 and 17 were subdivided.

A portion of the east boundary of the township and subdivisional lines were dependently resurveyed by Lynn M. Roseberry, in 1968.

A portion of the subdivisional lines were dependently resurveyed, and section 23 was subdivided, by G. Steven Popken, in 1975.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions, dated July 24, 1979, under Group Number 990, Oregon.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations.

The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming a closure were measured twice to preclude error. Only those lines bounding or crossing public lands were blazed.

The geographic position of the 1/4 section corner of sections 3 and 34, on the south boundary of the township, as determined from a traverse tie to Douglas County, 2nd order, Horizontal Control Station "ANT", are as follows:

Latitude 43° 15' 27.3" N. Longitude 122° 55' 14.0" W.