

County Surveyor's Record, Douglas County, Oregon

16938

T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	<p style="text-align: center;">The mean magnetic declination is 19° 45' E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the South Boundary, T. 26 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/> <p style="text-align: center;">(Restoring the survey by Samuel C. Flint, U.S. Deputy Surveyor, in 1882, the resurvey by Charles M. Collier, U.S. Surveyor, in 1913-14, and the dependent resurvey by Harold D. Corbin, in 1957)</p> <hr/> <p>Beginning at the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 5 ft. base, 2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 2 W</p> <p style="text-align: center;">1/4 $\frac{S\ 34}{S\ 3}$</p> <p style="text-align: center;">T 27 S 1957</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A fir, 46 ins. diam., bears N. 10° W., 15 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 55 ins. diam., bears S. 10° W., 30 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Corbin</p> <p style="padding-left: 40px;">A madrone, 15 ins. diam., bears N. 49 1/2° E., 66 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 55 ins. diam., bears S. 23 1/4° W., 77 lks. dist., with healed blaze.</p> <p>From this point, Douglas County Horizontal Control Station "ANT", bears S. 23° 04' W., 54.43 chs. dist., monumented with a brass tablet, 2 1/2 ins. diam., firmly cemented into drill hole, in the NE. cor. of U.S.F.S. concrete bridge, mkd. COUNTY SURVEYORS OFFICE "ANT" 1974.</p> <p>S. 87° 58' W., bet. secs. 3 and 34, marking and blazing true line.</p> <p>Descend 250 ft. over broken SW. slope, through heavy timber and moderate undergrowth.</p> <p>10.90 Spur, slopes S. 40° W.; desc. 395 ft. over SW. slope.</p> <p>19.32 Point for the W 1/16 sec. cor. of secs. 3 and 34.</p> <p style="padding-left: 40px;">Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S\ 34}{S\ 3}$</p> <p style="text-align: center;">1979</p> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 12 ins. diam., bears N. 14 1/2° W., 30 lks. dist., mkd. W 1/16 S34 BT.</p>
--------	--