

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the
Subdivisional Lines, T. 26 S., R. 4 W.,
Willamette Meridian, Oregon

16940

CHAINS

(Restoring the survey by John A. McQuinn, U.S. Deputy Surveyor, in 1883, the survey by William N. Gibb in 1909-10, the corrective survey by Fred Mensch, U.S. Surveyor, in 1916, and the dependent resurvey by Irving Zirpel, Jr. and William W. Glenn, Cadastral Surveyors, in 1959)

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp.

N. 0° 37' W., bet. secs. 33 and 34, marking and blazing the true line.

Ascend 330 ft. over SW. slope, through heavy timber and dense undergrowth.

19.63 Point for the S. 1/16 sec. cor. of secs. 33 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 33 | S 34
1979

*FD OK
1/2001
B. Shaver
CS 65/36-2B
M 132-70*

from which

A grand fir, 11 ins. diam., bears N. 31 3/4° E.,
7 1/2 lks. dist., mkd. S 1/16 S34 BT.

A grand fir, 9 ins. diam., bears N. 67 1/4° W., 14
lks. dist., mkd. S 1/16 S33 BT.

Cor. is located on top of spur, slopes S. 10° E. from N.; asc. 135 ft. over S. slope along spur top.

36.20 Leave top, spur slopes S. from N. 20° W.; desc. 35 ft. along broken E. slope.

39.26 The 1/4 sec. cor. of secs. 33 and 34, perpetuated and recorded by Thomas E. Shrum, Jr., Registered Engineer No. 4287, in 1978, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd.

RE 4287
1/4 COR
T 26 S S 33 | S 34
R 2 W
1978

from which the remains of an original bearing tree

A fir, 22 ins. diam., bears S. 67° W., 58 lks.
dist., with scribe marks BT visible on opened
blaze. (Record, S. 64° W.)

and a bearing tree mkd. by Shrum

A fir, 16 ins. diam., bears S. 20 1/2° E., 43 1/2 lks.
dist., with scribe marks 1/4 S34 BT visible on
open blaze and a tag mkd. RE 4287.

N. 0° 01' W., beginning new measurement.

Ascend 120 ft. over SE. slope.