

County Surveyor's Record, Douglas County, Oregon

16943

Subdivision of Section 9,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
1.30	Ravine, drains N. 65° W.; asc. 15 ft. over SW. slope.
2.60	Spur, slopes N. 60° W.; desc. 300 ft. over NW. slope.
20.05	Honey Creek Road, gravelled, 20 lks. wide, bears N. 25° E. and S. 25° W.
20.92	Point for the center S 1/16 sec. cor. of sec. 9. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} C \\ S\ 1/16 \quad \quad S\ 9 \\ C \\ 1979 \end{array}$
	from which
	A fir, 18 ins. diam., bears N. 22 1/2° E., 20 lks. dist., mkd. CS 1/16 S9 BT.
	A hemlock, 11 ins. diam., bears N. 14° W., 21 lks. dist., mkd. CS 1/16 S9 BT.
	Descend 10 ft. over NW. slope.
21.95	Bottom of descent, drains West; asc. 50 ft. over SW. slope.
30.35	Spur, slopes W.; desc. 55 ft. over broken NW. slope.
39.25	Honey Creek, 20 lks. wide, course S. 30° W.; asc. 25 ft. over SE. slope.
40.85	Skid road, 15 lks. wide, bears N. 5° E. and S. 5° W.
41.84	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} T\ 26\ S \quad R\ 2\ W \\ C\ 1/4 \quad S\ 9 \\ 1979 \end{array}$
	from which
	A fir, 19 ins. diam., bears N. 46 1/2° E., 33 lks. dist., mkd. C 1/4 S9 BT.
	A grand fir, 13 ins. diam., bears N. 40 1/2° W., 16 1/2 lks. dist., mkd. C 1/4 S9 BT.
	Ascend 345 ft. over SE. slope.
63.95	Spur, slopes N. 85° E.; desc. 60 ft. over NE. slope.
68.55	Creek, 2 lks. wide, course S. 20° E.; asc. 190 ft. over SW. slope.
74.35	Spur, slopes E.; desc. 15 ft. over NE. slope.
77.15	Ravine, drains S. 50° E.; asc. 200 ft. over S. slope.

BLM
FD. B.C. #2875
3/26/92
C.S. 63/140