

County Surveyor's Record, Douglas County, Oregon

16946

Subdivision of Section 9,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	<p>From the E 1/16 sec. cor. of secs. 9 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S \ 9}{S \ 16}$ 1959</p> <p>from which bearing trees mkd. by Zirpel and Glenn</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 47° W., 23 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears N. 87° W., 39 lks. dist., with healed blaze. (Record, N. 82° W.)</p> <p>N. 1° 27' E., on the N. and S. center line of the SE 1/4 of sec. 9.</p> <p>Ascend 135 ft. over SE. slope, through heavy timber and dense undergrowth.</p>
16.25	Spur, slopes S. 55° W.; desc. 25 ft. over NW. slope.
17.90	Top of rock bluff, 60 ft. high, edge bears N. 50° E. and S. 50° W.; desc. 185 ft. over NW. slope.
20.84	<p>Point for the SE 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of the SE 1/4 of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 9 1979</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 63 1/2° E., 41 lks. dist., mkd. SE 1/16 S9 BT.</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears S. 68° E., 26 1/2 lks. dist., mkd. SE 1/16 S9 BT</p> <p>Descend 325 ft. over NW. slope.</p>
41.68	The center E 1/16 sec. cor. of sec. 9.
	<p>From the S 1/16 sec. cor. of secs. 9 and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 9 S 10 1959</p> <p>from which bearing trees by Zirpel and Glenn</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 53° E., 48 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears S. 71° W., 18 lks. dist., with scribe marks S 1/16 S9 BT visible on open blaze.</p>