

# County Surveyor's Record, Douglas County, Oregon

16947

Subdivision of Section 9,  
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	<p>S. 89° 04' W., on the E. and W. center line of the SE 1/4 of sec. 9.</p> <p>Ascend 30 ft. over broken SE. slope, through heavy timber and dense undergrowth.</p>
13.85	Spur, slopes S. 40° W.; desc. 180 ft. over NW. slope.
18.85	Top of rock bluff, 60 ft. high, edge bears N. 15° E. and S. 15° W.; desc. 40 ft. over NW. slope.
19.47	<p>The SE. 1/16 sec. cor. of sec. 9.</p> <p>Descend 490 ft. over NW. slope.</p>
38.30	Honey Creek Road, gravelled, 20 lks. wide, bears N. 30° E. and S. 30° W.
38.96	The center S 1/16 sec. cor. of sec. 9.
	<p>From the W 1/16 sec. cor. of secs. 9 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">W \frac{1}{16} \quad \frac{S \ 9}{S \ 16}</math> <p>1959</p> </div> <p>from which the bearing trees mkd. by Zirpel and Glenn</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 17° E., 19 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears S. 65° W., 4 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>N. 1° 17' E., on the N. and S. center line of the SW 1/4 of sec. 9.</p> <p>Ascend 135 ft. over SE. slope, through heavy timber and dense undergrowth.</p>
16.00	Ravine, drains SE.; asc. 120 ft. over SW. slope.
21.02	<p>Point for the SW 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of the SW 1/4 of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">SW \frac{1}{16} \quad S \ 9</math> <p>1979</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 19° W., 30 lks. dist., mkd. SW 1/16 S9 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 31 1/2° W., 19 1/2 lks. dist., mkd. SW 1/16 S9 BT.</p> <p>Ascend 60 ft. over SW. slope.</p>
23.50	Spur, slopes S. 85° E.; desc. 35 ft. over NE. slope.