

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of South Boundary,
T. 21 S., R. 4 W., Willamette Meridian, Oregon

16952

CHAINS

T 21 S R 4 W

1/4 $\frac{S\ 35}{S\ 2}$

T 22 S R 4 W
1965

from which the remains of the original bearing trees

A root hole, bears N. 30° E., 4 lks. dist., with a
downed sawed fir stump alongside, 38 ins. diam.,
with fragmentary scribe marks visible on
opened blaze.

A sawed fir stump, 35 ins. diam., bears S. 4° W.,
24 lks. dist., with fragmentary scribe marks
visible on bark.

bearing trees mkd. by Godfrey

A fir, 22 ins. diam., bears N. 49° E., 79 1/2 lks.
dist., with healed double blaze.

A fir, 25 ins. diam., bears N. 73° W., 40 lks.
dist., with healed double blaze.

a bearing tree mkd. by Jelley

A grand fir, 22 ins. diam., bears S. 3° E., 147 lks.
dist., with healed blaze.

and a new bearing tree

A fir, 7 ins. diam., bears S. 16 1/2° W., 22 lks.
dist., mkd. 1/4 S2 BT.

S. 89° 58' W., on the S. bdy. of sec. 35, marking and
blazing the true line.

Descend 90 ft. over NW. slope, through heavy timber and
dense undergrowth.

6.15 Bottom of descent, slopes N.; asc. 30 ft. over NE. slope.

11.75 Ravine, drains N.; asc. 60 ft. over NE slope.

15.90 Spur, slopes N. 30° E.; desc. 295 ft. over NW. slope.

35.85 Ravine, drains S.; asc. 80 ft. over SE. slope.

37.39 True point for the closing cor. of secs. 2 and 3,
T. 22 S., R. 4 W., described in the field notes of the
dependent resurvey of a portion of the subdivisional
lines of T. 22 S., R. 4 W., executed concurrently under
this same Group.

40.56 The cor. of secs. 34 and 35 only, perpetuated and
recorded by Milo E. Godfrey, Deputy County Surveyor, in
1962, monumented with an iron post, 1 1/4 ins. diam., firmly
set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 21 S R 4 W

S 34 | S 35

1962