

# County Surveyor's Record, Douglas County, Oregon

16353

Dependent Resurvey, Portion of South Boundary,  
T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A fir, 22 ins. diam., bears N. 77 1/2° E., 43 lks. dist., with healed blaze. (Record, N. 83° E.)

A sawed fir stump, 42 ins. diam., bears S. 55° W., 34 lks. dist., no marks visible (Record, S. 50° W.)

A madrone, 25 ins. diam., bears N. 48° W., 42 lks. dist., with fragmentary scribe marks visible on open blaze.

a bearing tree mkd. by Thiel

A sawed fir stump, 32 ins. diam., bears S. 87° E., 68 lks. dist., no marks visible.

and bearing trees mkd. by Godfrey

A cedar, 23 ins. diam., bears N. 62° E., 42 lks. dist., with fragmentary scribe marks visible on open blaze.

A fir, 13 ins. diam., bears N. 22° W., 23 1/2 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, oak, cedar, yew, pine, alder, maple, hemlock, chinquapin, and ash; undergrowth, vine maple, Oregon grape, poison oak, blackberry, thimbleberry, wild rose, salmonberry, arrowwood, hazel, ferns, and young timber.

S. 89° 48' W., on the S. bdy. of sec. 34.

Ascend 5 ft. over SE. slope, through heavy timber and dense undergrowth.

0.75 Spur, slopes S. 20° W.; desc. 135 ft. over SW. slope.

9.75 Ravine, drains S. 25° W.; asc. 80 ft. over E. slope.

12.25 Spur, slopes S. 20° W.; desc. 55 ft. over SW. slope.

20.02 Point for the E 1/16 sec. cor. of sec. 3 only, T. 22 S., R. 4 W.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 S 3

1980

from which

A fir, 5 ins. diam., bears S. 65° E., 39 lks. dist., mkd. E 1/16 S3 BT.

A grand fir, 18 ins. diam., bears S. 89° W., 60 lks. dist., mkd. E 1/16 S3 BT.

Descend 245 ft. over SW. slope.