

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of South Boundary,
T. 21 S., R. 4 W., Willamette Meridian, Oregon

16354

CHAINS	
31.50	Ravine, drains S. 50° W.; asc. 20 ft. over SE. slope.
40.04	<p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 S R 4 W</p> <p>1/4 $\frac{S\ 34}{S\ 3}$</p> <p>T 22 S R 4 W</p> <p>1980</p> </div> <div style="text-align: right; margin-top: 10px;"> <p><i>ADOK</i> <i>BY Donald Peel</i> <i>7/88 M. 106-48</i></p> </div> <p>from which</p> <p style="margin-left: 40px;">A grand fir, 16 ins. diam., bears North, 47 1/2 lks. dist., mkd. 1/4 S34 BT.</p> <p style="margin-left: 40px;">A grand fir, 16 ins. diam., bears S. 18 1/2° W., 70 lks. dist., mkd. 1/4 S3 BT.</p> <p>Ascend 5 ft. over SE. slope.</p>
41.40	Spur, slopes S. 20° W.; desc. 265 ft. over SW. slope.
57.20	Gravelled road, 30 lks. wide, bears N. 55° W. and S. 65° E.
59.85	Creek, 2 lks. wide, course N. 20° W.; desc. 5 ft. over SW. slope.
60.06	<p>Point for the W 1/16 sec. cor. of secs. 3 and 34.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, cemented in a drill hole, in bedrock, with top mkd.</p> <div style="text-align: center;"> <p>W 1/16 $\frac{S\ 34}{S\ 3}$</p> <p>1980</p> </div> <p>from which</p> <p style="margin-left: 40px;">A hemlock 12 ins. diam., bears N. 13 1/4° E., 85 lks. dist., mkd. W 1/16 S34 BT.</p> <p style="margin-left: 40px;">A yew, 18 ins. diam., bears S. 52° W., 32 1/2 lks. dist., mkd. W 1/16 S3 BT.</p> <p>Descend 25 ft. over SW. slope.</p>
63.35	Creek, 2 lks. wide, course N. 15° W.; asc. 290 ft. over NE. slope.
74.20	Ridge, bears N. 60° W. and S. 60° E.; desc. 85 ft. over SW. slope.
80.08	<p>Point for the cor. of secs. 3, 4, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>