

# County Surveyor's Record, Douglas County, Oregon

16955

Dependent Resurvey, Portion of South Boundary,  
T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

FD ok  
By Donald Peel  
7/88 M106-48

T 21 S R 4 W

S 33	S 34
S 4	S 3

T 22 S R 4 W

1980

from which

A cedar, 6 ins. diam., bears N. 56° E., 30 lks.  
dist., mkd. T21S R4W S34 BT.

A cedar, 6 ins. diam., bears S. 53 3/4° E., 27 lks.  
dist., mkd. T22S R4W S3 BT.

A fir, 12 ins. diam., bears S. 55 1/2° W., 45 lks.  
dist., mkd. T22S R4W S4 BT.

A fir, 6 ins. diam., bears N. 33 1/2° W., 59 lks.  
dist., mkd. T21S R4W S33 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, yew, maple, alder, madrone, oak, and ash; undergrowth, poison oak, blackberry, Oregon grape, salmonberry, arrowwood, hazel, ferns, and young timber.

S. 89° 48' W., bet. secs. 4 and 33.

Descend 320 ft. over SW. slope, through heavy timber and dense undergrowth.

7.15 3 wire power transmission line, bears N. 20° E. and S. 20° W., also dirt road, 20 lks. wide, bears N. and S.

11.80 Dirt road, 20 lks. wide, bears N. 65° W. and S. 40°-E.

16.25 Creek, 3 lks. wide, course N. 20° W.; asc. 245 ft. over SE. slope.

23.65 Spur, slopes N. 30° E.; desc. 190 ft. over NW. slope.

29.30 Creek, 2 lks. wide, course N. 20° E.; asc. 305 ft. over SE. slope.

38.40 Ridge, bears N. 10° E. and S. 10° W.; desc. 5 ft. over SW. slope.

40.04 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S R 4 W

1/4	S 33	
	S 4	S 3

T 22 S R 4 W

1980

from which

A fir, 10 ins. diam., bears S. 51 1/2° W., 74 lks.  
dist., mkd. 1/4 S4 BT.