

# County Surveyor's Record, Douglas County, Oregon

16957

Dependent Resurvey of  
a Portion of the Subdivisional Lines,  
T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Harvey Gordon and  
Charles T. Gardner, U.S. Deputy Surveyors, in 1855)

From the cor. of secs. 34 and 35 only, on the S. bdy. of the Tp.

N. 1° 06' E., bet. secs. 34 and 35, marking and blazing the true line.

Ascend 20 ft. over SE. slope, through heavy timber and dense undergrowth.

1.25 Spur, slopes NW.; desc. 30 ft. over NE. slope.

3.25 Ravine, drains S. 65° E.; asc. 20 ft. over SE. slope.

5.45 Spur, slopes NW.; desc. 235 ft. over NW. slope.

21.20 Spur, slopes NW.; desc. 175 ft. over NW. slope.

27.70 Creek, 2 lks. wide, course N. 75° W.; asc. 225 ft. over SE. slope.

39.96 The 1/4 sec. cor. of secs. 34 and 35, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1957, monumented with an iron rod, 5/8 ins diam., firmly set, projecting 8 ins. above ground, from which the remains of an original bearing tree

A root hole, bears S. 87° W., 12 lks. dist., with a down fir alongside, 5 ins. diam., with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by Byron

A cedar, 25 ins. diam., bears N. 80° E., 86 1/2 lks. dist., with healed blaze.

A grand fir, 18 ins. diam., bears N. 32° W., 55 1/2 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S R 4 W

$\frac{1}{4}$   
 S 34 | S 35  
 1980

from which new bearing trees

A grand fir, 6 ins. diam., bears S. 69° E., 10 lks. dist., mkd. 1/4 S35 BT.

A fir, 6 ins. diam., bears N. 62° W., 19 lks. dist., mkd. 1/4 S34 BT.

Reset iron rod alongside the iron post.

N. 0° 11' E., beginning new measurement.

Ascend 90 ft. over SE. slope.