

# County Surveyor's Record, Douglas County, Oregon

**16959**

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 21 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 21 S	R 4 W
S 22	S 23
S 27	S 26

1980

from which new bearing trees

A fir, 12 ins. diam., bears N. 1° E., 36 1/2 lks. dist., mkd. T21S R4W S23 BT.

A fir, 27 ins. diam., bears S. 36° E., 67 lks. dist., mkd. T21S R4W S26 BT.

A fir, 12 ins. diam., bears S. 50 1/2° W., 25 lks. dist., mkd. T21S R4W S27 BT.

A fir, 9 ins. diam., bears N. 36° W., 41 lks. dist., mkd. T21S R4W S22 BT.

N. 0° 17' W., bet. secs. 22 and 23.

Descend 40 ft. over NE. slope, through heavy timber and dense undergrowth.

4.30 Bottom of descent, slopes E.; asc. 85 ft. over broken SE. slope.

17.55 Spur, slopes NE.; desc. 135 ft. over NW. slope.

28.85 Ravine, drains W. 30° E.; desc. 155 ft. over NE. slope.

37.20 Ravine, drains E.; asc. 25 ft. over SE. slope.

38.65 Wire fence, extends E. and W.

40.30 Spur, slopes N. 60° E.; desc. slightly over NW. slope.

40.39 Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S	R 4 W
1/4	
S 22	S 23

1980

from which

A fir, 10 ins. diam., bears N. 89 1/2° E., 36 lks. dist., mkd. 1/4 S23 BT.

A fir, 13 ins. diam., bears S. 24 1/2° W., 28 lks. dist., mkd. 1/4 S22 BT.

Descend 120 ft. over NW. slope.